

ZC-T5Q10X-SG

Smart Alarm Bullet Camera

Feature:

- ◆ 5.0MP H.265+,24 hours Day/Night full-color vision
- ◆ AI Human body detection, triggering light alarm when a human is detected, significantly reduce the false alarm rate.
- ◆ Two-way audio;
- ◆ F1.4 advanced aperture, optimize image brightness, with better performance in low-light environments
- ◆ Support 3 modes of night vision: Smart dual light/infrared/full-color night vision
- ◆ Quick target search for playback



Chip parameters	
Model	ZC-T5Q10X-SG
Product Name	Smart Alarm Bullet Camera
System Structure	Embedded RTOS design, dual core;32 bits DSP,pure hardware compression, watch dog,16MB FLASH,128MB DDR3;
Sensor	5MP 1/2.7" CMOS,0.001Lux@F1.2(color),0Lux(IR ON);integrate IR-CUT drive, support linkage control between Sensor &IR-CUT& photosensitive& LED fill light, support day/night switch;
Video Process	H.265+/H.265/H.264 video coding, support dual stream, AVI format; code stream 500k~8M bps adjustable, support PAL and NTSC
Frame Rates	5MP and 4MP@25 FPS;3MP and below @30FPS
Image Output	Main stream :2880×1620, 2592×1520, 2560×1440, 2048×1520, 2304×1296, 1920×1080 Main stream :800×448, 720×480, 640×480, 640×360, 480×360, 352×288
Audio code	G.711 CODEC standard, support audio and video synchronization,2-way audio
Network protocols	HTTP,TCP/IP,IPv4,DHCP,NTP,RTSP,ONVIF,P2P,PPTP,SMTP,GB/T28181,etc.
Business Functions	Configure by WEB, OSD(on screen display),real-time video transmission, motion detection; support remote surveillance client software(Seetong);support mobile monitoring(Iphone, Android),support "Seetong" cloud service;
ONVIF Protocol	Support
Client	Support iOS, Android, PC client
AI function	Human body detection, Vehicle Detection(optional), support regional intrusion & cross-border detection
External parameters	
Fill Light	12*Dot-Matrix infrared light LED +12*Dot-Matrix white light LED..
Ethernet interfaces	1*RJ45 Ethernet interface,10/100M self-adaption,8KV anti-static electric capacity;
Lightning protection	Surge protection in power supply and network, front end power input, lightning protection,anti-static,anti-inverse connect, support 18V turn off voltage protection;
Power supply	DC12V power input interface,anti-inverse connect, support 18V turn off voltage protection;
Operating Temperature	-40°C~+85°C
Protection Level	IP66
Power Consumption	Daytime≤ 1.7W Max; Night≤3.8W Max

Size(mm)	90mm*115mm*185mm
Weight	NW:360g GW:460g

Product structure:

